



Bearing No. 238/1000 CAMA/W20

| | |
|-------------------------------|-------------------|
| K | 12 mm |
| d | 1000 mm |
| D | 1220 mm |
| B | 165 mm |
| Size (mm) | 1220x1000x165 |
| Width (mm) | 165 |
| Mass bearing | 410 kg |
| D_1 | 1161 mm |
| d_2 | 1079 mm |
| Bearing number | 238/1000 CAMA/W20 |
| Limiting speed | 400 r/min |
| Reference speed | 220 r/min |
| r_a max. | 5 mm |
| D_a max. | 1197 mm |
| d_a min. | 1023 mm |
| Bore Diameter (mm) | 1220 |
| Outer Diameter (mm) | 1000 |
| r_a - max. | 5 mm |
| Calculation factor e | 0.12 |
| d_a - min. | 1023 mm |
| D_a - max. | 1197 mm |
| $r_{1,2}$ min. | 6 mm |
| D_1 ? | 1161 mm |
| d_2 ? | 1079 mm |
| $r_{1,2}$ - min. | 6 mm |
| Calculation factor - e | 0.12 |
| Basic dynamic load rating C | 5405 kN |
| Basic dynamic load rating - C | 5405 kN |
| | |

| | |
|-------------------------------------|----------|
| Fatigue load limit P_u | 850 kN |
| Calculation factor Y_1 | 5.6 |
| Calculation factor Y_2 | 8.4 |
| Calculation factor Y_0 | 5.6 |
| Calculation factor - Y_0 | 5.6 |
| Calculation factor - Y_2 | 8.4 |
| Calculation factor - Y_1 | 5.6 |
| Fatigue load limit - P_u | 850 kN |
| Basic static load rating C_0 | 14300 kN |
| Basic static load rating - C_0 | 14300 kN |