



Bearing No. GEZM 010 ES

D	26.988 mm
d	15.875 mm
B	23.8 mm
C	11.913 mm
b	3.2 mm
M	2.5 mm
?	9 °
?	9 °
Size (mm)	26.988x15.875x23.8
Lubricant	Regular relubrication – grease
Width (mm)	23,8
b ₁	3 mm
b ₁	3 mm
d _k	22.835 mm
d ₁	19.812 mm
d _k	22.835 mm
Bearing number	GEZM 010 ES
Sealing solution	-
d _a max.	19.8 mm
d _a min.	18.4 mm
r ₂ min.	1 mm
r ₁ min.	0.6 mm
D _a min.	21.7 mm
D _a max.	23.6 mm
r _a max.	0.6 mm
r _b max.	1 mm
Mass plain bearing	0.041 kg
Bore Diameter (mm)	26,988
Outer Diameter (mm)	15,875

d_a - min.	18.4 mm
r_2 - min.	1 mm
r_1 - min.	0.6 mm
r_b - max.	1 mm
r_a - max.	0.6 mm
D_a - max.	23.6 mm
D_a - min.	21.7 mm
d_a - max.	19.8 mm
d_1 ?	19.812 mm
Constant - K_M	330
Basic dynamic load rating C	21.6 kN
Basic dynamic load rating - C	21.6 kN
Specific dynamic load factor K	100 N/mm ²
Material constant K_M	330
Specific factor dynamic load - K	100 N/mm ²
Basic static load rating C_0	65.5 kN
Basic static load rating - C_0	65.5 kN
Specific static load factor K_0	300 N/mm ²
Specific factor static load - K_0	300 N/mm ²
Design (sliding contact surface combination)	Steel/steel