



Bearing No. JL725346/JL725316

e	0.48
d	125 mm
D	175 mm
T	25,4 mm
B	25,4 mm
C	18,288 mm
a	34,3 mm
Da	161 mm
B_	25.4
Db	168 mm
da	138 mm
Y0	0.69
db	133 mm
C0	232
D_	175
Z_	35
C_	18.288
Y1	1.3
DE_	159.371
SLR	16.5
D_a	161
DI_	71.16
DA1	11.459
DA2	10.765
CUP	0.573
DA_	11.114
D_b	168
RAr	271.697
SDM_	148.691
KBRG	3141

yobi	JL725346/JL725316
CONE	1.19
ALP21	35
ALP22	12
ALP23	0
BETA_	1
BET21	2
BET23	0
BET22	25
r min.	3,3 mm
LangID	1
Weight	1,763 Kg
ALPHA_	17.6
r1 min.	3,3 mm
ra max.	3,3 mm
Oil rpm	2400
outer r	3.3
hidYobi	JL725346/JL725316
GRS rpm	1800
inner r	3.3
hidTable	ecat_NSTPRI
inner ra	3.3
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	125x175x25.4
SHOG_yobi	JL725346R/JL725316R
Prod_Type3	TRBSR_ID_A
Width (mm)	25,4
Bearing number	JL725346/JL725316
Bore Diameter (mm)	125
Outer Diameter (mm)	175
Calculation factor (e)	0,48

(Oil) Lubrication Speed	2400 r/min
Calculation factor (Y0)	0,69
(Grease) Lubrication Speed	1800 r/min
Basic static load rating (C0)	232 kN
Basic dynamic load rating (C)	134 kN