



Bearing No. GEZH 104 ES-2LS

D	61.913 mm
d	31.75 mm
B	35.306 mm
C	28.575 mm
b	4.8 mm
M	4 mm
?	8 °
?	8 °
Size (mm)	61.913x31.75x35.306
Lubricant	Regular relubrication – grease
Width (mm)	35,306
b ₁	5 mm
b ₁	5 mm
d _k	54.737 mm
d _k	54.737 mm
Bearing number	GEZH 104 ES-2LS
Sealing solution	Triple-lip seals
d _a max.	41.8 mm
d _a min.	36.2 mm
r ₂ min.	1 mm
r ₁ min.	1 mm
D _a min.	52.3 mm
D _a max.	58 mm
r _a max.	1 mm
r _b max.	1 mm
Mass plain bearing	0.54 kg
Bore Diameter (mm)	61,913
Outer Diameter (mm)	31,75
d _a - min.	36.2 mm

r_2 - min.	1 mm
r_1 - min.	1 mm
r_b - max.	1 mm
r_a - max.	1 mm
D_a - max.	58 mm
D_a - min.	52.3 mm
d_a - max.	41.8 mm
Constant - K_M	330
Basic dynamic load rating C	125 kN
Basic dynamic load rating - C	125 kN
Specific dynamic load factor K	100 N/mm ²
Material constant K_M	330
Specific factor dynamic load - K	100 N/mm ²
Basic static load rating C_0	375 kN
Basic static load rating - C_0	375 kN
Specific static load factor K_0	300 N/mm ²
Specific factor static load - K_0	300 N/mm ²
Design (sliding contact surface combination)	Steel/steel