



Bearing No. NUP2326EM

r	4
D	280 mm
C	93 mm
S	2,3 mm
B	93 mm
d	130 mm
Fw	167 mm
Z_	14
r1	4
da	146
C0	1230
ra	3
rb	3
B_	93
D_	280
DA_	40
DE_	247
DI_	167
yobi	NUP2326EM
mass	30.6
SDM_	207
KBRG	4165
SBRG	23
db min	146 mm
C_conv	920000
Db max	264 mm
r min.	4 mm
ALPHA_	0
LangID	1
dd min	184

dc min	169
Weight	30 Kg
db max	163
da min.	146 mm
D_a max	264
r1 min.	4 mm
rb max.	3 mm
TSR rpm	2400
Da max.	264 mm
GRS rpm	1900
Oil rpm	2400
ra max.	3 mm
hidYobi	NUP2326EM
db max.	163 mm
hidTable	ecat_NSCLDR
Macha rpm	3800
Size (mm)	130x280x93
Prod_Type3	CRB_SR_NUP
Width (mm)	93
Bearing number	NUP2326EM
Bore Diameter (mm)	130
Outer Diameter (mm)	280
(Grease) Lubrication Speed	1900 r/min
Basic static load rating (C0)	1230 kN
Basic dynamic load rating (C)	920 kN