



Bearing No. 230/1120-B-MB

|                     |                                           |
|---------------------|-------------------------------------------|
| m                   | 2210 kg / Weight                          |
| d                   | 1120 mm                                   |
| D                   | 1580 mm                                   |
| B                   | 345 mm                                    |
| e                   | 0,2                                       |
| Size (mm)           | 1120x1580x345                             |
| Width (mm)          | 345                                       |
| $n_s$               | 23,5 mm                                   |
| $Y_1$               | 3,42                                      |
| $Y_2$               | 5,09                                      |
| $D_1$               | 1445,4 mm                                 |
| $d_s$               | 12,5 mm                                   |
| $Y_0$               | 3,34                                      |
| $n_G$               | 350 1/min / Limiting speed                |
| $n_B$               | 183 1/min / Reference speed               |
| $C_r$               | 14900000 N / Dynamic load rating (radial) |
| $C_{0r}$            | 37500000 N / Static load rating (radial)  |
| Bearing number      | 230/1120-B-MB                             |
| $C_{ur}$            | 2260000 N                                 |
| $r_{min}$           | 9,5 mm                                    |
| $r_{a \max}$        | 8 mm                                      |
| $d_{a \min}$        | 1154 mm                                   |
| $D_{a \max}$        | 1546 mm                                   |
| Bore Diameter (mm)  | 1120                                      |
| Outer Diameter (mm) | 1580                                      |

