



Bearing No. 23284-B-K-MB + H3284-HG

| | |
|----------------|--|
| d | 420 mm |
| l | 352 mm |
| D | 760 mm |
| B | 272 mm |
| c | 70 mm |
| m | 539 kg / Weight |
| e | 0,38 |
| Size (mm) | 400x760x272 |
| Width (mm) | 272 |
| n_B | 920000 N / Fatigue limit load, radial |
| C_r | 6550000 N / Dynamic load rating (radial) |
| n_s | 23,5 mm |
| d_s | 12,5 mm |
| D_1 | 642,2 mm |
| D_m | 540 mm |
| Y_1 | 1,77 |
| c_1 | 89 mm |
| Y_2 | 2,64 |
| Y_0 | 1,73 |
| n_G | 760 1/min / Limiting speed |
| m_1 | 95,3 kg |
| C_{0r} | 12200000 N / Static load rating (radial) |
| Bearing number | 23284-B-K-MB + H3284-HG |
| d_{1H} | 400 mm |
| r_{min} | 7,5 mm |

| | |
|-----------------------------|--------------------------|
| $r_{a \max}$ | 6 mm |
| $d_{a \max}$ | 495 mm |
| $D_{a \max}$ | 728 mm |
| $B_{a \min}$ | 16 mm |
| $d_{b \min}$ | 449 mm |
| Bore Diameter (mm) | 400 |
| Outer Diameter (mm) | 760 |
| - H3284-HG / Adapter sleeve | H3284HG / Adapter sleeve |