



Bearing No. 53310

| | |
|-------------|------------|
| T | 34.3 |
| d | 50 mm |
| D | 95 mm |
| C | - |
| A | 28 mm |
| R | 72 mm |
| Ca | 121 |
| Cu | 9.10 |
| T1 | 34,3 mm |
| d1 | 95 mm |
| D1 | 52 mm |
| Coa | 202 |
| Weight | 1,01 Kg |
| r(min) | 1.1 |
| r min. | 1,1 mm |
| d1(max) | 95 |
| D1(min) | 52 |
| D2(min) | - |
| ra max. | 1 mm |
| da(min) | 77 |
| D3(min) | - |
| Da max. | 68 mm |
| da min. | 77 mm |
| Da(max) | 68 |
| ra(max) | 1 |
| Oil lub. | 2700 |
| Size (mm) | 50x95x34.3 |
| Width (mm) | 34,3 |
| Bearing No. | 53310 |
| Grease lub. | 1800 |
| | |

| | |
|-------------------------------|------------|
| Bearing number | 53310 |
| (Refer.)Mass(kg) | 1.01 |
| Bore Diameter (mm) | 50 |
| Outer Diameter (mm) | 95 |
| (Grease) Lubrication Speed | 1800 r/min |
| Basic dynamic load rating (C) | 96,6 kN |
| Basic static load rating (C0) | 202 kN |