



### Bearing No. 53310U

C	97.5
D	95 mm
R	72 mm
A	28 mm
T	37 mm
b	11 mm
d	50 mm
r	1.1
A_	28
D_	95
Z_	13
da	77
T3	34.3
C0	202
T4	37
ra	1
B_	37
R_	72
D2	72 mm
D3	100 mm
D1	52 mm
d1	95 mm
D_2	72
D_3	100
SRE	8.57
D_1	52
SRI	8.57
DA_	15.875
D_a	68
SREX	0.065

SRIN	0
SREN	0
mass	1.27
yobi	53310U
SDM_	72.5
SRIX	0.065
KBRG	5131
r min.	1,1 mm
LangID	1
Weight	1,27 Kg
ra max.	1 mm
GRS rpm	1800
Oil rpm	2800
da min.	77 mm
Da max.	68 mm
hidYobi	53310U
hidTable	ecat_NSSDTB
Size (mm)	50x95x37
Prod_Type3	TB_SD_WASW
Width (mm)	37
Bearing number	53310U
Bore Diameter (mm)	50
Outer Diameter (mm)	95
(Grease) Lubrication Speed	1800 r/min
Basic static load rating (C0)	202 kN
Basic dynamic load rating (C)	97,5 kN