



Bearing No. 53312

R	90 mm
C	119
r	1.1
d	60 mm
D	110 mm
T	38,3 mm
A	41 mm
R_	90
B_	38.3
ra	1
C0	263
da	90
Z_	14
A_	41
T3	38.3
d1	110 mm
D_	110
D1	62 mm
D_1	62
DA_	17.462
SRI	9.4
SRE	9.4
D_a	80
SREN	0
SRIN	0
yobi	53312
SRIX	0.065
mass	1.51
SDM_	85
KBRG	5121

SREX	0.065
Noun	Bearing
Bore 1	2.362 Inch 60 Millimeter
Height	1.496 Inch 38 Millimeter
Banded	No
UNSPSC	31171552
r min.	1,1 mm
LangID	1
Bore 2	2.441 Inch 62 Millimeter
Weight	1,51 Kg
GRS rpm	1600
hidYobi	53312
Oil rpm	2400
ra max.	1 mm
Da max.	80 mm
da min.	90 mm
Category	Thrust Ball Bearings
hidTable	ecat_NSSDTB
Size (mm)	60x110x38.3
Inventory	0.0
Prod_Type3	TB_SD_WAS
Width (mm)	38,3
Weight / LBS	3.32898
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	53312
Other Features	Single Row With Aligning Seat
Thrust Bearing	Yes

Keyword String	Ball Thrust
Rolling Element	Ball Bearing
Precision Class	Non-Precision
Manufacturer URL	http://www.nskamericas.com
Long Description	60MM Bore 1; 62MM Bore 2; 110MM Outside Diameter; 38MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Outside Diameter	4.331 Inch 110 Millimeter
Weight / Kilogram	1.78
Manufacturer Name	NSK
Bore Diameter (mm)	60
Outer Diameter (mm)	110
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Plus Raceways
Harmonized Tariff Code	8482.10.50.08
(Grease) Lubrication Speed	1600 r/min
Single or Double Direction	Single Direction
Basic static load rating (C0)	263 kN
Basic dynamic load rating (C)	119 kN
Overall Height with Aligning Washer	0 Inch 0 Millimeter