



### Bearing No. 53415

R	125 mm
C	254
r	2
d	75 mm
D	160 mm
T	69 mm
A	42 mm
R_	125
B_	69
ra	2
C0	560
da	125
Z_	10
A_	42
T3	69
d1	160 mm
D_	160
D1	78 mm
D_1	78
DA_	30.162
SRI	16.3
SRE	16.3
D_a	110
SREN	0
SRIN	0
yobi	53415
SRIX	0.125
mass	6.23
SDM_	117.5
KBRG	5121

SREX	0.125
Noun	Bearing
Height	2.717 Inch   69 Millimeter
Bore 1	2.953 Inch   75 Millimeter
Banded	No
UNSPSC	31171552
r min.	2 mm
LangID	1
Bore 2	3.071 Inch   78 Millimeter
Weight	6,23 Kg
GRS rpm	950
hidYobi	53415
Oil rpm	1400
ra max.	2 mm
Da max.	110 mm
da min.	125 mm
Category	Thrust Ball Bearings
hidTable	ecat_NSSDTB
Size (mm)	75x160x69
Inventory	0.0
Prod_Type3	TB_SD_WAS
Width (mm)	69
Weight / LBS	13.7348
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	53415
Other Features	Single Row   With Aligning Seat
Thrust Bearing	Yes

Keyword String	Ball Thrust
Rolling Element	Ball Bearing
Precision Class	Non-Precision
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Long Description	75MM Bore 1; 78MM Bore 2; 160MM Outside Diameter; 69MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Outside Diameter	6.299 Inch   160 Millimeter
Weight / Kilogram	7.87
Manufacturer Name	NSK
Bore Diameter (mm)	75
Outer Diameter (mm)	160
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Plus Raceways
Harmonized Tariff Code	8482.10.50.08
(Grease) Lubrication Speed	950 r/min
Single or Double Direction	Single Direction
Basic static load rating (C0)	560 kN
Basic dynamic load rating (C)	254 kN
Overall Height with Aligning Washer	0 Inch   0 Millimeter