



Bearing No. GEZ 600 TXA-2LS

D	222.25 mm
d	152.4 mm
B	120.65 mm
C	104.775 mm
?	5 °
?	5 °
Size (mm)	222.25x152.4x120.65
Lubricant	Maintenance free – dry lubrication
Width (mm)	120,65
d _k	207.162 mm
d _k	207.162 mm
Bearing number	GEZ 600 TXA-2LS
Sealing solution	Triple-lip seals
D _a max.	211 mm
D _a min.	203.5 mm
d _a max.	168 mm
d _a min.	161.5 mm
r ₂ min.	1.1 mm
r ₁ min.	1 mm
r _a max.	1 mm
r _b max.	1.1 mm
Mass plain bearing	17.5 kg
Bore Diameter (mm)	222,25
Outer Diameter (mm)	152,4
d _a - min.	161.5 mm
r _b - max.	1.1 mm
r _a - max.	1 mm
D _a - max.	211 mm
D _a - min.	203.5 mm

d _a - max.	168 mm
r ₂ - min.	1.1 mm
r ₁ - min.	1 mm
Basic dynamic load rating C	2600 kN
Basic dynamic load rating - C	2600 kN
Specific dynamic load factor K	150 N/mm ²
Specific factor dynamic load - K	150 N/mm ²
Basic static load rating C ₀	5200 kN
Basic static load rating - C ₀	5200 kN
Specific static load factor K ₀	300 N/mm ²
Specific factor static load - K ₀	300 N/mm ²
Design (sliding contact surface combination)	Steel/PTFE fabric