



Bearing No. SYJ 65 TF

| | |
|----------------|---------------|
| L | 265 mm |
| J | 203 mm |
| d | 65 mm |
| A | 70 mm |
| N | 35 mm |
| B | 68,3 mm |
| G | 20 mm |
| H | 151 mm |
| N1 | 25 mm |
| H2 | 27 mm |
| H1 | 76,2 mm |
| A1 | 49 mm |
| s1 | 42,9 mm |
| UNSPSC | 31171511 |
| Weight | 6,15 Kg |
| J max. | 213 mm |
| J min. | 193 mm |
| Category | Bearings |
| Inventory | 0.0 |
| H ₂ | 27 mm |
| A ₁ | 49 mm |
| N ₁ | 25 mm |
| s ₁ | 42.9 mm |
| B ₄ | 10 mm |
| H ₁ | 76.2 mm |
| J ₇ | 23 mm |
| D _N | 6.5 mm |
| Product Group | M06110 |
| G _N | 1/4-28 SAE-LT |
| J ₆ | 241 mm |
| | |

| | |
|---|------------|
| R_1 | 5.5 mm |
| N_4 | 4 mm |
| R_G | 1/4-28 UNF |
| $R_?$ | 45 ° |
| SW_N | 7 mm |
| Limiting speed | 3000 r/min |
| Bearing number | SYJ 65 TF |
| Housing material | Cast iron |
| Weight / Kilogram | 0 |
| Manufacturer Name | SKF |
| Mass bearing unit | 5.7 kg |
| Bore Diameter (mm) | 65 |
| Minimum Buy Quantity | N/A |
| Fatigue load limit (Pu) | 1,7 |
| Basic dynamic load rating C | 57.2 kN |
| Basic static load rating (C0) | 40 kN |
| Basic dynamic load rating (C) | 57,2 kN |
| Thread grub screw G_2 | M10x1 |
| Fatigue load limit P_u | 1.7 kN |
| Hexagonal key size for grub screw N | 5 mm |
| Basic static load rating C_0 | 40 kN |
| Recommended tightening torque for grub screw | 16.5 N·m |
| Recommended diameter for attachment bolts, mm G | 20 mm |
| Recommended diameter for attachment bolts, inch G | 0.75 in |