



Bearing No. 53320U

| | |
|------|--------|
| C | 239 |
| D | 170 mm |
| R | 125 mm |
| A | 46 mm |
| T | 64 mm |
| b | 18 mm |
| d | 100 mm |
| r | 1.5 |
| A_ | 46 |
| D_ | 170 |
| Z_ | 15 |
| da | 142 |
| T3 | 59.2 |
| C0 | 595 |
| T4 | 64 |
| ra | 1.5 |
| B_ | 64 |
| R_ | 125 |
| D2 | 135 mm |
| D3 | 175 mm |
| D1 | 103 mm |
| d1 | 170 mm |
| D_2 | 135 |
| D_3 | 175 |
| SRE | 13.7 |
| D_1 | 103 |
| SRI | 13.7 |
| DA_ | 25.4 |
| D_a | 128 |
| SREX | 0.1 |

| | |
|-------------------------------|-------------|
| SRIN | 0 |
| SREN | 0 |
| mass | 6.37 |
| yobi | 53320U |
| SDM_ | 135 |
| SRIX | 0.1 |
| KBRG | 5131 |
| r min. | 1,5 mm |
| LangID | 1 |
| Weight | 6,37 Kg |
| ra max. | 1,5 mm |
| GRS rpm | 1000 |
| Oil rpm | 1500 |
| da min. | 142 mm |
| Da max. | 128 mm |
| hidYobi | 53320U |
| hidTable | ecat_NSSDTB |
| Size (mm) | 100x170x64 |
| Prod_Type3 | TB_SD_WASW |
| Width (mm) | 64 |
| Bearing number | 53320U |
| Bore Diameter (mm) | 100 |
| Outer Diameter (mm) | 170 |
| (Grease) Lubrication Speed | 1000 r/min |
| Basic static load rating (C0) | 595 kN |
| Basic dynamic load rating (C) | 239 kN |