



Bearing No. HR33124J

D	200 mm
d	120 mm
T	62 mm
B	62 mm
C	48 mm
a	47,9 mm
e	0.4
Cr	46500
Y0	0.83
db	133
da	135
Y1	1.5
B_	62
Sb	14
C0	755
Sa	9
D_	200
Z_	23
C_	48
C0r	77000
DA_	19.826
Iso	3FE
DE_	178.856
D_b	192
DI_	140.23
SBRG	31
SDM_	159.543
D_a2	173
KBRG	3111
yobi	HR33124J

D_a1	190
mass	7.67
TC-RA	372.508
r min.	2,5 mm
Weight	7,67 Kg
TC-DA1	21.126
TC-DA2	18.526
TC-SLR	46
Da min	173 mm
LangID	1
ALPHA_	14.833
Db min.	192 mm
Oil rpm	2400
db max.	133 mm
Da max.	190 mm
ra max.	2 mm
hidYobi	HR33124J
da min.	135 mm
T-ALP21	29
rb max.	2 mm
T-ALP22	40
T-ALP23	0
GRS rpm	1700
inner r	2.5
outer r	2
r1 min.	2 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	2
outer rb	2
TC-BET22	15

Size (mm)	120x200x62
Width (mm)	62
Prod_Type3	TRBSR_MD_A
Bearing number	HR33124J
Bore Diameter (mm)	120
Outer Diameter (mm)	200
Calculation factor (e)	0,4
Calculation factor (Y0)	0,83
(Oil) Lubrication Speed	2400 r/min
(Grease) Lubrication Speed	1700 r/min
Basic dynamic load rating (C)	460 kN
Basic static load rating (C0)	755 kN