



Bearing No. HR332/32J

D	65 mm
d	32 mm
T	26 mm
B	26 mm
C	20,5 mm
a	17 mm
e	0.35
Cr	7150
Y0	0.95
db	38
da	41
Y1	1.7
B_	26
Sb	5.5
C0	86.5
Sa	5
D_	65
Z_	17
C_	20.5
C0r	8850
DA_	8.056
Iso	2DE
DE_	56.524
D_b	62
DI_	40.772
SBRG	32
SDM_	48.648
D_a2	55
KBRG	3111
yobi	HR332/32J

D_a1	59
mass	0.4
TC-RA	135.22
r min.	1 mm
Weight	0,4 Kg
TC-DA1	8.652
TC-DA2	7.459
TC-SLR	18.7
Da min	55 mm
LangID	1
ALPHA_	13
Db min.	62 mm
Oil rpm	8000
db max.	38 mm
Da max.	59 mm
ra max.	1 mm
hidYobi	HR332/32J
da min.	41 mm
T-ALP21	26
rb max.	1 mm
T-ALP22	0
T-ALP23	0
GRS rpm	5600
inner r	1
outer r	1
r1 min.	1 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	1
outer rb	1
TC-BET22	40

Size (mm)	32x65x26
Width (mm)	26
Prod_Type3	TRBSR_MD_A
Bearing number	HR332/32J
Bore Diameter (mm)	32
Outer Diameter (mm)	65
Calculation factor (e)	0,35
Calculation factor (Y0)	0,95
(Oil) Lubrication Speed	8000 r/min
(Grease) Lubrication Speed	5600 r/min
Basic dynamic load rating (C)	70 kN
Basic static load rating (C0)	86,5 kN