



Bearing No. HR33206J

D	62 mm
d	30 mm
T	25 mm
B	25 mm
C	19,5 mm
a	16,1 mm
e	0.34
Cr	6800
Y0	0.97
db	35
da	39
Y1	1.8
B_	25
Sb	5.5
C0	79.5
Sa	5
D_	62
Z_	16
C_	19.5
C0r	8100
DA_	8.14
Iso	2DE
DE_	53.966
D_b	59.5
DI_	38.029
SBRG	32
SDM_	45.998
D_a2	52
KBRG	3111
yobi	HR33206J

D_a1	56
mass	0.355
TC-RA	130.808
r min.	1 mm
Weight	0,355 Kg
TC-DA1	8.75
TC-DA2	7.53
TC-SLR	18.3
Da min	52 mm
LangID	1
ALPHA_	12.833
Db min.	59,5 mm
Oil rpm	8000
db max.	35 mm
Da max.	56 mm
ra max.	1 mm
hidYobi	HR33206J
da min.	39 mm
T-ALP21	25
rb max.	1 mm
T-ALP22	40
T-ALP23	0
GRS rpm	6000
inner r	1
outer r	1
r1 min.	1 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	1
outer rb	1
TC-BET22	50

Size (mm)	30x62x25
Width (mm)	25
Prod_Type3	TRBSR_MD_A
Bearing number	HR33206J
Bore Diameter (mm)	30
Outer Diameter (mm)	62
Calculation factor (e)	0,34
Calculation factor (Y0)	0,97
(Oil) Lubrication Speed	8000 r/min
(Grease) Lubrication Speed	6000 r/min
Basic dynamic load rating (C)	66,5 kN
Basic static load rating (C0)	79,5 kN