



Bearing No. HR33207J

D	72 mm
d	35 mm
T	28 mm
B	28 mm
C	22 mm
a	18,3 mm
e	0.35
Cr	8850
Y0	0.93
db	41
da	46
Y1	1.7
B_	28
Sb	6
C0	108
Sa	5
D_	72
Z_	17
C_	22
C0r	11100
DA_	9.103
Iso	2DE
DE_	62.367
D_b	68
DI_	44.483
SBRG	32
SDM_	53.425
D_a2	61
KBRG	3111
yobi	HR33207J

D_a1	63
mass	0.54
TC-RA	146.401
r min.	1,5 mm
Weight	0,54 Kg
TC-DA1	9.792
TC-DA2	8.413
TC-SLR	20.7
Da min	61 mm
LangID	1
ALPHA_	13.25
Db min.	68 mm
Oil rpm	7100
db max.	41 mm
Da max.	63 mm
ra max.	1,5 mm
hidYobi	HR33207J
da min.	46 mm
T-ALP21	26
rb max.	1,5 mm
T-ALP22	30
T-ALP23	0
GRS rpm	5300
inner r	1.5
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	1.5
outer rb	1.5
TC-BET22	50

Size (mm)	35x72x28
Width (mm)	28
Prod_Type3	TRBSR_MD_A
Bearing number	HR33207J
Bore Diameter (mm)	35
Outer Diameter (mm)	72
Calculation factor (e)	0,35
Calculation factor (Y0)	0,93
(Oil) Lubrication Speed	7100 r/min
(Grease) Lubrication Speed	5300 r/min
Basic dynamic load rating (C)	86,5 kN
Basic static load rating (C0)	108 kN