



Bearing No. HR33208J

D	80 mm
d	40 mm
T	32 mm
B	32 mm
C	25 mm
a	20,8 mm
e	0.36
Cr	10900
Y0	0.92
db	46
da	51
Y1	1.7
B_	32
Sb	7
C0	137
Sa	5
D_	80
Z_	17
C_	25
C0r	14000
DA_	10.005
Iso	2DE
DE_	69.369
D_b	76
DI_	49.751
SBRG	32
SDM_	59.56
D_a2	67
KBRG	3111
yobi	HR33208J

D_a1	71
mass	0.744
TC-RA	161.38
r min.	1,5 mm
Weight	0,744 Kg
TC-DA1	10.794
TC-DA2	9.215
TC-SLR	23.7
Da min	67 mm
LangID	1
ALPHA_	13.417
Db min.	76 mm
Oil rpm	6300
db max.	46 mm
Da max.	71 mm
ra max.	1,5 mm
hidYobi	HR33208J
da min.	51 mm
T-ALP21	26
rb max.	1,5 mm
T-ALP22	50
T-ALP23	0
GRS rpm	4800
inner r	1.5
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	1.5
outer rb	1.5
TC-BET22	50

Size (mm)	40x80x32
Width (mm)	32
Prod_Type3	TRBSR_MD_A
Bearing number	HR33208J
Bore Diameter (mm)	40
Outer Diameter (mm)	80
Calculation factor (e)	0,36
Calculation factor (Y0)	0,92
(Oil) Lubrication Speed	6300 r/min
(Grease) Lubrication Speed	4800 r/min
Basic dynamic load rating (C)	107 kN
Basic static load rating (C0)	137 kN