



Bearing No. HR33213J

D	120 mm
d	65 mm
T	41 mm
B	41 mm
C	32 mm
a	29,2 mm
e	0.39
Cr	20600
Y0	0.85
db	74
da	77
Y1	1.5
B_	41
Sb	9
C0	282
Sa	6
D_	120
Z_	19
C_	32
C0r	28800
DA_	14.069
Iso	3EE
DE_	106.189
D_b	115
DI_	78.38
SBRG	32
SDM_	92.285
D_a2	102
KBRG	3111
yobi	HR33213J

D_a1	111
mass	2.04
TC-RA	225.533
r min.	2 mm
Weight	2,04 Kg
TC-DA1	15.085
TC-DA2	13.053
TC-SLR	30.5
Da min	102 mm
LangID	1
ALPHA_	14.583
Db min.	115 mm
Oil rpm	4000
db max.	74 mm
Da max.	111 mm
ra max.	2 mm
hidYobi	HR33213J
da min.	77 mm
T-ALP21	29
rb max.	1,5 mm
T-ALP22	10
T-ALP23	0
GRS rpm	3000
inner r	2
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	2
outer rb	1.5
TC-BET22	50

Size (mm)	65x120x41
Width (mm)	41
Prod_Type3	TRBSR_MD_A
Bearing number	HR33213J
Bore Diameter (mm)	65
Outer Diameter (mm)	120
Calculation factor (e)	0,39
Calculation factor (Y0)	0,85
(Oil) Lubrication Speed	4000 r/min
(Grease) Lubrication Speed	3000 r/min
Basic dynamic load rating (C)	202 kN
Basic static load rating (C0)	282 kN