



Bearing No. HR33215J

D	130 mm
d	75 mm
T	41 mm
B	41 mm
C	31 mm
a	31,6 mm
e	0.43
Cr	21900
Y0	0.77
db	83
da	87
Y1	1.4
B_	41
Sb	10
C0	315
Sa	7
D_	130
Z_	21
C_	31
C0r	32000
DA_	14.069
Iso	3EE
DE_	115.516
D_b	125
DI_	87.963
SBRG	32
SDM_	101.74
D_a2	111
KBRG	3111
yobi	HR33215J

D_a1	121
mass	2.25
TC-RA	225.533
r min.	2 mm
Weight	2,25 Kg
TC-DA1	15.085
TC-DA2	13.053
TC-SLR	30.5
Da min	111 mm
LangID	1
ALPHA_	15.917
Db min.	125 mm
Oil rpm	3800
db max.	83 mm
Da max.	121 mm
ra max.	2 mm
hidYobi	HR33215J
da min.	87 mm
T-ALP21	31
rb max.	1,5 mm
T-ALP22	50
T-ALP23	0
GRS rpm	2800
inner r	2
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	2
outer rb	1.5
TC-BET22	50

Size (mm)	75x130x41
Width (mm)	41
Prod_Type3	TRBSR_MD_A
Bearing number	HR33215J
Bore Diameter (mm)	75
Outer Diameter (mm)	130
Calculation factor (e)	0,43
Calculation factor (Y0)	0,77
(Oil) Lubrication Speed	3800 r/min
(Grease) Lubrication Speed	2800 r/min
Basic dynamic load rating (C)	215 kN
Basic static load rating (C0)	315 kN