



Bearing No. 53412

R	100 mm
C	202
r	1.5
d	60 mm
D	130 mm
T	54 mm
A	34 mm
R_	100
B_	54
ra	1.5
C0	395
da	102
Z_	10
A_	34
T3	54
d1	130 mm
D_	130
D1	62 mm
D_1	62
DA_	25.4
SRI	13.7
SRE	13.7
D_a	88
SREN	0
SRIN	0
yobi	53412
SRIX	0.1
mass	3.2
SDM_	95
KBRG	5121

SREX	0.1
Noun	Bearing
Bore 2	2.441 Inch 62 Millimeter
Height	2.126 Inch 54 Millimeter
Banded	No
UNSPSC	31171552
r min.	1,5 mm
LangID	1
Weight	3,2 Kg
Bore 1	2.362 Inch 60 Millimeter
GRS rpm	1200
hidYobi	53412
Oil rpm	1800
ra max.	1,5 mm
Da max.	88 mm
da min.	102 mm
Category	Thrust Ball Bearings
hidTable	ecat_NSSDTB
Size (mm)	60x130x54
Inventory	0.0
Prod_Type3	TB_SD_WAS
Width (mm)	54
Weight / LBS	7.05479
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Bearing number	53412
Other Features	Single Row With Aligning Seat
Thrust Bearing	Yes

Keyword String	Ball Thrust
Rolling Element	Ball Bearing
Precision Class	Non-Precision
Manufacturer URL	http://www.nskamericas.com
Long Description	60MM Bore 1; 62MM Bore 2; 130MM Outside Diameter; 54MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; Non-Precision
Outside Diameter	5.118 Inch 130 Millimeter
Weight / Kilogram	4.13
Manufacturer Name	NSK
Bore Diameter (mm)	60
Outer Diameter (mm)	130
Minimum Buy Quantity	N/A
Component Description	Roller Assembly Plus Raceways
Harmonized Tariff Code	8482.10.50.08
(Grease) Lubrication Speed	1200 r/min
Single or Double Direction	Single Direction
Basic static load rating (C0)	395 kN
Basic dynamic load rating (C)	202 kN
Overall Height with Aligning Washer	0 Inch 0 Millimeter