



Bearing No. GEZ 304 TXE-2LS

D	130.175 mm
d	82.55 mm
B	72.238 mm
C	61.9 mm
?	6 °
?	6 °
Size (mm)	130.175x82.55x72.238
Lubricant	Maintenance free – dry lubrication
Width (mm)	72,238
d _k	118.745 mm
d _k	118.745 mm
Bearing number	GEZ 304 TXE-2LS
Sealing solution	Triple-lip seals
D _a max.	122.7 mm
D _a min.	118.8 mm
d _a max.	94.2 mm
d _a min.	88.4 mm
r ₂ min.	1 mm
r ₁ min.	0.6 mm
r _a max.	0.6 mm
r _b max.	1 mm
Mass plain bearing	3.8 kg
Bore Diameter (mm)	130,175
Outer Diameter (mm)	82,55
d _a - min.	88.4 mm
r _b - max.	1 mm
r _a - max.	0.6 mm
D _a - max.	122.7 mm
D _a - min.	118.8 mm

d_a - max.	94.2 mm
r_2 - min.	1 mm
r_1 - min.	0.6 mm
Basic dynamic load rating C	880 kN
Basic dynamic load rating - C	880 kN
Specific dynamic load factor K	150 N/mm ²
Specific factor dynamic load - K	150 N/mm ²
Basic static load rating C_0	1760 kN
Basic static load rating - C_0	1760 kN
Specific static load factor K_0	300 N/mm ²
Specific factor static load - K_0	300 N/mm ²
Design (sliding contact surface combination)	Steel/PTFE fabric