



Bearing No. GEZ 204 TXE-2LS

C	42.85 mm
d	57.15 mm
D	90.488 mm
B	50.013 mm
?	6 °
Bore	2.25 Inch 57.15 Millimeter
Noun	Bearing
UNSPSC	31171515
?	6 °
Category	Plain Bearings Spherical Radial
Inventory	0.0
Lubricant	Maintenance free – dry lubrication
Enclosure	2 Seals
Size (mm)	90.488x57.15x50.013
Keyword 3	Spherical
Width (mm)	50,013
Weight / LBS	2.87
Inch - Metric	Inch
Self Aligning	Yes
Overall Width	1.969 Inch 50.013 Millimeter
Product Group	B04264
Housing Width	1.687 Inch 42.85 Millimeter
dk	82.169 mm
dk	82.169 mm
Keyword String	Plain Spherical Radial
Other Features	2 Piece Chrome Plated Ball Self Lubricating

	Triple Lip Heavy Duty Seals
Bearing number	GEZ 204 TXE-2LS
Relubricatable	No
Rolling Element	Spherical Plain
Material - Ball	Steel
Outside Diameter	3.563 Inch 90.5 Millimeter
Long Description	2-1/4" Bore; 1-11/16" Housing Width; 3-9/16" Outside Diameter; Steel Outer Member; Steel Ball; Teflon Liner; 1-31/32" Overall Width; Not Relubricatable
Sealing solution	Triple-lip seals
Material - Liner	Teflon
Manufacturer URL	http://www.skf.com
Weight / Kilogram	1.3
Manufacturer Name	SKF
Mass plain bearing	1.3 kg
r _b max.	1 mm
D _a max.	84.1 mm
D _a min.	81.9 mm
d _a max.	65.1 mm
d _a min.	62 mm
r ₂ min.	1 mm
r ₁ min.	0.6 mm
Bore Diameter (mm)	90,488
r _a max.	0.6 mm
Outer Diameter (mm)	57,15
d _a - max.	65.1 mm
Minimum Buy Quantity	N/A
D _a - min.	81.9 mm
r ₂ - min.	1 mm

r_1 - min.	0.6 mm
D_a - max.	84.1 mm
r_a - max.	0.6 mm
r_b - max.	1 mm
d_a - min.	62 mm
Harmonized Tariff Code	8483.30.80.70
Material - Outer Member	Steel
Manufacturer Item Number	GEZ 204 TXE-2LS
Basic dynamic load rating C	425 kN
Basic dynamic load rating - C	425 kN
Specific dynamic load factor K	150 N/mm ²
Specific factor dynamic load - K	150 N/mm ²
Basic static load rating C_0	850 kN
Basic static load rating - C_0	850 kN
Specific static load factor K_0	300 N/mm ²
Specific factor static load - K_0	300 N/mm ²
Design (sliding contact surface combination)	Steel/PTFE fabric