



Bearing No. HR33019J

D	145 mm
d	95 mm
T	39 mm
B	39 mm
C	32,5 mm
a	28,6 mm
e	0.28
Cr	23500
Y0	1.2
db	103
da	107
Y1	2.2
B_	39
Sb	6.5
C0	390
Sa	7
D_	145
Z_	28
C_	32.5
C0r	39500
DA_	12.68
Iso	2CE
DE_	132.37
D_b	139
DI_	107.319
SBRG	30
SDM_	119.845
D_a2	133
KBRG	3111
yobi	HR33019J

D_a1	136
mass	2.3
TC-RA	378
r min.	2 mm
Weight	2,3 Kg
TC-DA1	13.194
TC-DA2	12.166
TC-SLR	29.5
Da min	133 mm
LangID	1
ALPHA_	10.5
Db min.	139 mm
Oil rpm	3200
db max.	103 mm
Da max.	136 mm
ra max.	2 mm
hidYobi	HR33019J
da min.	107 mm
T-ALP21	21
rb max.	1,5 mm
T-ALP22	0
T-ALP23	0
GRS rpm	2400
inner r	2
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	2
inner ra	2
outer rb	1.5
TC-BET22	0

Size (mm)	95x145x39
Width (mm)	39
Prod_Type3	TRBSR_MD_A
Bearing number	HR33019J
Bore Diameter (mm)	95
Outer Diameter (mm)	145
Calculation factor (e)	0,28
Calculation factor (Y0)	1,2
(Oil) Lubrication Speed	3200 r/min
(Grease) Lubrication Speed	2400 r/min
Basic dynamic load rating (C)	231 kN
Basic static load rating (C0)	390 kN