



Bearing No. HR33108J

D	75 mm
d	40 mm
T	26 mm
B	26 mm
C	20,5 mm
a	18 mm
e	0.36
Cr	8000
Y0	0.93
db	46
da	51
Y1	1.7
B_	26
Sb	5.5
C0	101
Sa	4
D_	75
Z_	18
C_	20.5
C0r	10300
DA_	8.574
Iso	2CE
DE_	66.028
D_b	71
DI_	49.137
SBRG	31
SDM_	57.583
D_a2	65
KBRG	3111
yobi	HR33108J

D_a1	66
mass	0.503
TC-RA	152.569
r min.	1,5 mm
Weight	0,503 Kg
TC-DA1	9.141
TC-DA2	8.006
TC-SLR	19
Da min	65 mm
LangID	1
ALPHA_	13.333
Db min.	71 mm
Oil rpm	6700
db max.	46 mm
Da max.	66 mm
ra max.	1,5 mm
hidYobi	HR33108J
da min.	51 mm
T-ALP21	26
rb max.	1,5 mm
T-ALP22	40
T-ALP23	0
GRS rpm	4800
inner r	1.5
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	1.5
outer rb	1.5
TC-BET22	26

Size (mm)	40x75x26
Width (mm)	26
Prod_Type3	TRBSR_MD_A
Bearing number	HR33108J
Bore Diameter (mm)	40
Outer Diameter (mm)	75
Calculation factor (e)	0,36
Calculation factor (Y0)	0,93
(Oil) Lubrication Speed	6700 r/min
(Grease) Lubrication Speed	4800 r/min
Basic dynamic load rating (C)	78,5 kN
Basic static load rating (C0)	101 kN