



Bearing No. SYK 40 TF

d	40 mm
A	48 mm
B	49,2 mm
G	12 mm
H	99 mm
J	136 mm
L	176 mm
N	21,5 mm
N1	14,5 mm
s1	30,2 mm
A1	30 mm
H1	49,2 mm
H2	19 mm
J min.	129 mm
J max.	143 mm
UNSPSC	31171511
Weight	0,86 Kg
Category	Bearings
Inventory	0.0
S ₁	30.2 mm
N ₁	14.5 mm
A ₅	23.5 mm
H ₂	19 mm
H ₁	49.2 mm
Product Group	M06110
B ₄	8 mm
A ₁	30 mm
Limiting speed	4800 r/min
Bearing number	SYK 40 TF
Housing material	Composite

Manufacturer Name	SKF
Weight / Kilogram	0.875
Mass bearing unit	0.82 kg
Bore Diameter (mm)	40
Minimum Buy Quantity	N/A
Fatigue load limit (Pu)	0,8
Basic dynamic load rating C	30.7 kN
Basic static load rating (C0)	19 kN
Basic dynamic load rating (C)	30,7 kN
Thread grub screw G ₂	M8x1
Fatigue load limit P _u	0.8 kN
Hexagonal key size for grub screw N	4 mm
Basic static load rating C ₀	19 kN
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	12 mm
Recommended diameter for attachment bolts, inch G	0.5 in