



Bearing No. HR32930J

D	210 mm
d	150 mm
T	38 mm
B	38 mm
C	30 mm
a	36,5 mm
e	0.33
Cr	28600
Y0	1
db	163
da	165
Y1	1.8
B_	38
Sb	8
C0	520
Sa	7
D_	210
Z_	34
C_	30
C0r	53000
DA_	14.575
Iso	2DC
DE_	194.486
D_b	202
DI_	165.926
SBRG	29
SDM_	180.206
D_a2	196
KBRG	3111
yobi	HR32930J

D_a1	198
mass	4.05
TC-RA	469.5
r min.	2,5 mm
Weight	4,05 Kg
TC-DA1	15.022
TC-DA2	14.128
TC-SLR	28
Da min	196 mm
LangID	1
ALPHA_	12.333
Db min.	202 mm
Oil rpm	2000
db max.	163 mm
Da max.	198 mm
ra max.	2 mm
hidYobi	HR32930J
da min.	165 mm
T-ALP21	24
rb max.	2 mm
T-ALP22	40
T-ALP23	0
GRS rpm	1500
inner r	2.5
outer r	2
r1 min.	2 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	1
inner ra	2
outer rb	2
TC-BET22	50

Size (mm)	150x210x38
Width (mm)	38
Prod_Type3	TRBSR_MD_A
Bearing number	HR32930J
Bore Diameter (mm)	150
Outer Diameter (mm)	210
Calculation factor (e)	0,33
Calculation factor (Y0)	1
(Oil) Lubrication Speed	2000 r/min
(Grease) Lubrication Speed	1500 r/min
Basic dynamic load rating (C)	281 kN
Basic static load rating (C0)	520 kN