



Bearing No. HR32948J

D	320 mm
d	240 mm
T	51 mm
B	51 mm
C	39 mm
a	65,1 mm
e	0.46
Cr	51000
Y0	0.72
db	255
da	258
Y1	1.3
B_	51
Sb	12
C0	1040
Sa	9
D_	320
Z_	38
C_	39
C0r	107000
DA_	19.324
Iso	4EC
DE_	298.876
D_b	314
DI_	261.496
SBRG	29
SDM_	280.186
D_a2	297
KBRG	3111
yobi	HR32948J

D_a1	308
mass	11.1
TC-RA	530
r min.	3 mm
Weight	11,1 Kg
TC-DA1	20.041
TC-DA2	18.607
TC-SLR	38
Da min	297 mm
LangID	1
ALPHA_	17
Db min.	314 mm
Oil rpm	1300
db max.	255 mm
Da max.	308 mm
ra max.	2,5 mm
hidYobi	HR32948J
da min.	258 mm
T-ALP21	34
rb max.	2 mm
T-ALP22	0
T-ALP23	0
GRS rpm	950
inner r	3
outer r	2.5
r1 min.	2,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	2
inner ra	2.5
outer rb	2
TC-BET22	10

Size (mm)	240x320x51
Width (mm)	51
Prod_Type3	TRBSR_MD_A
Bearing number	HR32948J
Bore Diameter (mm)	240
Outer Diameter (mm)	320
Calculation factor (e)	0,46
Calculation factor (Y0)	0,72
(Oil) Lubrication Speed	1300 r/min
(Grease) Lubrication Speed	950 r/min
Basic dynamic load rating (C)	500 kN
Basic static load rating (C0)	1040 kN