



Bearing No. HR32304J

| | |
|------|----------|
| D | 52 mm |
| d | 20 mm |
| T | 22,25 mm |
| B | 21 mm |
| C | 18 mm |
| a | 13,9 mm |
| e | 0.3 |
| Cr | 4650 |
| Y0 | 1.1 |
| db | 26 |
| da | 33 |
| Y1 | 2 |
| B_ | 21 |
| Sb | 4 |
| C0 | 47.5 |
| Sa | 3 |
| D_ | 52 |
| Z_ | 13 |
| C_ | 18 |
| C0r | 4850 |
| DA_ | 7.713 |
| Iso | 2FD |
| DE_ | 43.118 |
| D_b | 48 |
| DI_ | 28.094 |
| SBRG | 23 |
| SDM_ | 35.606 |
| D_a2 | 42 |
| KBRG | 3111 |
| yobi | HR32304J |

| | |
|----------|-------------|
| D_a1 | 43 |
| mass | 0.241 |
| TC-RA | 117.977 |
| r min. | 1,5 mm |
| Weight | 0,241 Kg |
| TC-DA1 | 8.234 |
| TC-DA2 | 7.192 |
| TC-SLR | 15 |
| Da min | 42 mm |
| LangID | 1 |
| ALPHA_ | 11.31 |
| Db min. | 48 mm |
| Oil rpm | 11000 |
| db max. | 26 mm |
| Da max. | 43 mm |
| ra max. | 1,5 mm |
| hidYobi | HR32304J |
| da min. | 33 mm |
| T-ALP21 | 22 |
| rb max. | 1,5 mm |
| T-ALP22 | 37 |
| T-ALP23 | 12 |
| GRS rpm | 8000 |
| inner r | 1.5 |
| outer r | 1.5 |
| r1 min. | 1,5 mm |
| hidTable | ecat_NSTPRM |
| TC-BET23 | 0 |
| TC-BET21 | 4 |
| inner ra | 1.5 |
| outer rb | 1.5 |
| TC-BET22 | 0 |
| | |

| | |
|-------------------------------|-------------|
| Size (mm) | 20x52x22.25 |
| Width (mm) | 22,25 |
| Prod_Type3 | TRBSR_MD_A |
| Bearing number | HR32304J |
| Bore Diameter (mm) | 20 |
| Outer Diameter (mm) | 52 |
| Calculation factor (e) | 0,3 |
| Calculation factor (Y0) | 1,1 |
| (Oil) Lubrication Speed | 11000 r/min |
| (Grease) Lubrication Speed | 8000 r/min |
| Basic dynamic load rating (C) | 45,5 kN |
| Basic static load rating (C0) | 47,5 kN |