



Bearing No. HR32313J

D	140 mm
d	65 mm
T	51 mm
B	48 mm
C	39 mm
a	34 mm
e	0.35
Cr	27300
Y0	0.96
db	80
da	86
Y1	1.7
B_	48
Sb	12
C0	340
Sa	4
D_	140
Z_	16
C_	39
C0r	35000
DA_	18.851
Iso	2GD
DE_	120.756
D_b	130
DI_	84.002
SBRG	23
SDM_	102.379
D_a2	116
KBRG	3111
yobi	HR32313J

D_a1	128
mass	3.6
TC-RA	287
r min.	3 mm
Weight	3,6 Kg
TC-DA1	20.031
TC-DA2	17.67
TC-SLR	34
Da min	116 mm
LangID	1
ALPHA_	12.953
Db min.	130 mm
Oil rpm	3800
db max.	80 mm
Da max.	128 mm
ra max.	2,5 mm
hidYobi	HR32313J
da min.	86 mm
T-ALP21	25
rb max.	2 mm
T-ALP22	54
T-ALP23	20
GRS rpm	2800
inner r	3
outer r	2.5
r1 min.	2,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	2.5
outer rb	2
TC-BET22	0

Size (mm)	65x140x51
Width (mm)	51
Prod_Type3	TRBSR_MD_A
Bearing number	HR32313J
Bore Diameter (mm)	65
Outer Diameter (mm)	140
Calculation factor (e)	0,35
Calculation factor (Y0)	0,96
(Oil) Lubrication Speed	3800 r/min
(Grease) Lubrication Speed	2800 r/min
Basic dynamic load rating (C)	267 kN
Basic static load rating (C0)	340 kN