



Bearing No. 6007ZZ

D	62 mm
d	35 mm
B	14 mm
C	14 mm
rn	0,5 mm
Bore	1.378 Inch 35 Millimeter
Noun	Bearing
da max	42 mm
UNSPSC	31171504
Weight	0,155 Kg
r min.	1 mm
ra max.	1 mm
Da max.	57 mm
series:	60
da min.	40 mm
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Size (mm)	35x62x14
Inventory	0.0
Snap Ring	No
Width (mm)	14
bore type:	Round
maximum rpm:	14000 RPM
Weight / LBS	0.3373
Cage Material	Steel
Inch - Metric	Metric
closure type:	Double Shielded
Product Group	B00308
bore diameter:	35 mm

Keyword String	Ball
overall width:	14 mm
cage material:	Steel
fillet radius:	1 mm
Other Features	Deep Groove Shell Alvania Prelubricated
Bearing number	6007ZZ
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Long Description	35MM Bore; 62MM Outside Diameter; 14MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Manufacturer URL	http://www.ntnamerica.com
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.551 Inch 14 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
outside diameter:	62 mm
outer ring width:	14 mm
inner ring width:	14 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
Weight / Kilogram	0.16
Bore Diameter (mm)	35

Internal Clearance	C0-Medium
Outer Diameter (mm)	62
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	12000 rpm
static load capacity:	10300 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	16000 N
Internal Special Features	No
(Grease) Lubrication Speed	12 000 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	10,3 kN
Basic dynamic load rating (C)	16 kN
Maximum Capacity / Filling Slot	No