



Bearing No. HR32211J

D	100 mm
d	55 mm
T	26,75 mm
B	25 mm
C	21 mm
a	22,7 mm
e	0.41
Cr	11200
Y0	0.81
db	63
da	67
Y1	1.5
B_	25
Sb	5.5
C0	137
Sa	4
D_	100
Z_	19
C_	21
C0r	14000
DA_	11.869
Iso	3DC
DE_	88.507
D_b	95
DI_	65.478
SBRG	22
SDM_	76.993
D_a2	87
KBRG	3111
yobi	HR32211J

D_a1	91
mass	0.859
TC-RA	179
r min.	2 mm
Weight	0,859 Kg
TC-DA1	12.493
TC-DA2	11.244
TC-SLR	18
Da min	87 mm
LangID	1
ALPHA_	15.109
Db min.	95 mm
Oil rpm	5000
db max.	63 mm
Da max.	91 mm
ra max.	2 mm
hidYobi	HR32211J
da min.	67 mm
T-ALP21	30
rb max.	1,5 mm
T-ALP22	13
T-ALP23	8
GRS rpm	3600
inner r	2
outer r	1.5
r1 min.	1,5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	2
outer rb	1.5
TC-BET22	0

Size (mm)	55x100x26.75
Width (mm)	26,75
Prod_Type3	TRBSR_MD_A
Bearing number	HR32211J
Bore Diameter (mm)	55
Outer Diameter (mm)	100
Calculation factor (e)	0,41
Calculation factor (Y0)	0,81
(Oil) Lubrication Speed	5000 r/min
(Grease) Lubrication Speed	3600 r/min
Basic dynamic load rating (C)	110 kN
Basic static load rating (C0)	137 kN