



Bearing No. HR32217J

a	33,8 mm
e	0.42
d	85 mm
D	150 mm
T	38,5 mm
B	36 mm
C	30 mm
B_	36
da	100
Y0	0.79
C0	277
D_	150
Sb	8.5
Sa	5
db	96
Z_	19
Y1	1.4
C_	30
Cr	21400
DE_	133.37
Iso	3EC
DI_	99.855
C0r	28200
DA_	17.28
D_b	142
D_a2	131
SBRG	22
SDM_	116.613
D_a1	140
yobi	HR32217J

KBRG	3111
mass	2.64
TC-RA	260
r min.	2,5 mm
LangID	1
TC-DA2	16.413
Da min	131 mm
TC-SLR	25
ALPHA_	15.643
TC-DA1	18.147
Weight	2,64 Kg
T-ALP22	17
da min.	100 mm
r1 min.	2 mm
T-ALP21	31
db max.	96 mm
hidYobi	HR32217J
rb max.	2 mm
T-ALP23	4
Da max.	140 mm
Oil rpm	3200
GRS rpm	2200
ra max.	2 mm
inner r	2.5
Db min.	142 mm
outer r	2
inner ra	2
hidTable	ecat_NSTPRM
outer rb	2
Category	Bearings
TC-BET23	0
TC-BET21	4

TC-BET22	0
Inventory	0.0
Size (mm)	85x150x38.5
Prod_Type3	TRBSR_MD_A
Width (mm)	38,5
Product Group	B04334
Bearing number	HR32217J
Weight / Kilogram	0
Manufacturer Name	NSK
Bore Diameter (mm)	85
Outer Diameter (mm)	150
Minimum Buy Quantity	N/A
Calculation factor (e)	0,42
(Oil) Lubrication Speed	3200 r/min
Calculation factor (Y0)	0,79
(Grease) Lubrication Speed	2200 r/min
Basic dynamic load rating (C)	210 kN
Basic static load rating (C0)	277 kN