



Bearing No. 23012CE4

e	0.26
r	1.1
d	60 mm
D	95 mm
B	26 mm
C	26 mm
X1	1
Y3	2.6
X2	0.67
Y0	2.5
Z_	24
Y1	2.6
C0	141
X0	1
D_	95
Y2	3.9
ra	1
B_	26
DE_	86.707
DA_	8.5
SIR	9.5
DI_	69.956
bomp	23012CE4
ALP2	50
ALP1	9
ALP3	0
yobi	23012CE4
SDM_	78.332
KBRG	2322
SBRG	30

mass	0.68
ALPHA_	0.172
da min	67
r min.	1,1 mm
Weight	0,68 Kg
LangID	1
da max	68 mm
Da min	85 mm
Oil rpm	4500
ra max.	1 mm
D_a max	88
D_a min	85
da min.	67 mm
Da max.	88 mm
hidYobi	23012CE4
TSR rpm	4800
GRS rpm	3600
hidTable	ecat_NSSPHR
Macha rpm	0
Size (mm)	60x95x26
Width (mm)	26
Prod_Type3	SRB_CTB_CB
Bearing number	23012CE4
Bore Diameter (mm)	60
Outer Diameter (mm)	95
Calculation factor (e)	0,26
(Oil) Lubrication Speed	4500 r/min
Calculation factor (Y0)	2,5
Calculation factor (Y2)	3,9
(Grease) Lubrication Speed	3600 r/min
Basic dynamic load rating (C)	98,5 kN

Basic static load rating (C0)	141 kN
----------------------------------	--------