



**Bearing No. TCJT30-N**

d	30 mm
V	80 mm
U	50,2 mm
A	29 mm
H	142 mm
J	116,5 mm
L	80 mm
N	11,5 mm
A2	20 mm
d3	44 mm
A1	12 mm
B1	48,5 mm
Bore	1.181 Inch   30 Millimeter
Noun	Bearing
Seals	Double Triply
Weight	0,9 Kg
UNSPSC	31171501
Category	Flange Block
Inventory	0.0
Thread (Q)	Rp1/8
Bolt Spacing	4.587 Inch   116.5 Millimeter
Weight / LBS	2.205
Product Group	M06110
Inch - Metric	Metric
Housing Style	2 Bolt Flange Block
Relubricatable	Yes
Keyword String	Flanged
Other Features	Single Row   Radial   Extended Inner Race

	Metric   With Set Screw
Bearing number	TCJT30-N
Mounting Bolts	11.5 Millimeter
Rolling Element	Ball Bearing
Mounting Method	Eccentric Collar
Housing Material	Cast Iron
Long Description	2 Bolt Flange Block; 30MM Bore; 117MM Bolt Circle; 116.5MM Bolt Spacing; 1 Piece Solid; Eccentric Collar Mount; Cast Iron; Ball Bearing; 48.4MM Length Thru Bore; Relubricatable; Double Triply Seal
Length Thru Bore	1.906 Inch   48.4 Millimeter
Manufacturer URL	<a href="http://www.ina.com">http://www.ina.com</a>
Manufacturer Name	SCHAEFFLER GROUP
Weight / Kilogram	1
Insert Part Number	GE30KPPB3
Bore Diameter (mm)	30
Pilot Configuration	No Pilot
Minimum Buy Quantity	N/A
Housing Configuration	1 Piece Solid
Harmonized Tariff Code	8483.20.40.40
Manufacturer Item Number	TCJT30
Number of Mounting Holes	2
Cartridge Pilot Diameter	0 Inch   0 Millimeter
Expansion / Non-expansion	Non-expansion
Basic dynamic load rating (C)	19,5 kN

Nominal Bolt Circle Diameter Round	4.6 Inch   117 Millimeter
------------------------------------	---------------------------