



Bearing No. HR32048XJ

D	360 mm
d	240 mm
T	76 mm
B	76 mm
C	57 mm
a	79,1 mm
e	0.46
Cr	94000
Y0	0.72
db	262
da	261
Y1	1.3
B_	76
Sb	19
C0	1730
Sa	12
D_	360
Z_	29
C_	57
C0r	177000
DA_	29.375
Iso	4FD
DE_	327.783
D_b	346
DI_	271.259
SBRG	20
SDM_	299.521
D_a2	321
KBRG	3111
yobi	HR32048XJ

D_a1	346
mass	26.2
TC-RA	589
r min.	4 mm
Weight	26,2 Kg
TC-DA1	30.835
TC-DA2	27.914
TC-SLR	56
Da min	321 mm
LangID	1
ALPHA_	17
Db min.	346 mm
Oil rpm	1200
db max.	262 mm
Da max.	346 mm
ra max.	3 mm
hidYobi	HR32048XJ
da min.	261 mm
T-ALP21	34
rb max.	2,5 mm
T-ALP22	0
T-ALP23	0
GRS rpm	850
inner r	4
outer r	3
r1 min.	3 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	3
inner ra	3
outer rb	2.5
TC-BET22	0

Size (mm)	240x360x76
Width (mm)	76
Prod_Type3	TRBSR_MD_A
Bearing number	HR32048XJ
Bore Diameter (mm)	240
Outer Diameter (mm)	360
Calculation factor (e)	0,46
Calculation factor (Y0)	0,72
(Oil) Lubrication Speed	1200 r/min
(Grease) Lubrication Speed	850 r/min
Basic dynamic load rating (C)	920 kN
Basic static load rating (C0)	1730 kN