



### Bearing No. NUP2232EM

r	3
D	290 mm
C	80 mm
S	3,3 mm
B	80 mm
d	160 mm
Fw	193 mm
Z_	18
r1	3
da	173
C0	1190
ra	2.5
rb	2.5
B_	80
D_	290
DA_	34
DE_	261
DI_	193
yobi	NUP2232EM
mass	25.2
SDM_	227
KBRG	4165
SBRG	22
db min	173 mm
C_conv	810000
Db max	277 mm
r min.	3 mm
ALPHA_	0
LangID	1
dd min	210

dc min	197
Weight	24,5 Kg
db max	188
da min.	173 mm
D_a max	277
r1 min.	3 mm
rb max.	2,5 mm
TSR rpm	2400
Da max.	277 mm
GRS rpm	1900
Oil rpm	2400
ra max.	2,5 mm
hidYobi	NUP2232EM
db max.	188 mm
hidTable	ecat_NSCLDR
Macha rpm	3600
Size (mm)	160x290x80
Prod_Type3	CRB_SR_NUP
Width (mm)	80
Bearing number	NUP2232EM
Bore Diameter (mm)	160
Outer Diameter (mm)	290
(Grease) Lubrication Speed	1900 r/min
Basic static load rating (C0)	1190 kN
Basic dynamic load rating (C)	810 kN