

**Bearing No. 23026-E1A-K-M + AHX3026**

	AHX3026 / Designation, withdrawal sleeve
l	67 mm
a	4 mm
e	0,23
d	130 mm
b	14 mm
m	5,7 kg / Weight
B	52 mm
D	200 mm
Size (mm)	125x200x52
Width (mm)	52
Y <sub>0</sub>	2,89
D <sub>1</sub>	182,3 mm
m <sub>1</sub>	0,94 kg / Weight, withdrawal sleeve
Y <sub>2</sub>	4,4
Y <sub>1</sub>	2,95
d <sub>s</sub>	4,8 mm
n <sub>s</sub>	9,5 mm
n <sub>G</sub>	3600 1/min / Limiting speed
C <sub>r</sub>	540000 N / Dynamic load rating (radial)
n <sub>B</sub>	2650 1/min / Reference speed
C <sub>0r</sub>	730000 N / Static load rating (radial)
Bearing number	23026-E1A-K-M + AHX3026
d <sub>2G</sub>	M140X2

$d_{1H}$	125 mm
$C_{ur}$	70000 N / Fatigue limit load, radial
$r_{min}$	2 mm
$r_{a\ max}$	2 mm
$d_{a\ min}$	138,8 mm
$D_{a\ max}$	191,2 mm
Bore Diameter (mm)	125
Outer Diameter (mm)	200