



Bearing No. 30238JR

a	66,4 mm
C	46 mm
e	0.44
d	190 mm
D	340 mm
T	60 mm
B	55 mm
Cu	118
Db	318 mm
Cr	912
Y1	1.38
Y0	0.76
C0r	1030
a(mm)	66.4
r(min)	5
r min.	5 mm
Weight	21,9 Kg
da max	225 mm
Da min	298 mm
Da(min)	298
da(min)	212
r1(min)	4
Sb(min)	13
db(max)	225
Da(max)	322
Sa(min)	12
rb max.	3 mm
ra(max)	4
rb(max)	3
Db(min)	318

ra max.	4 mm
Db min.	318 mm
db max.	225 mm
Da max.	322 mm
da min.	212 mm
r2 min.	4 mm
r1 min.	4 mm
Oil lub.	1300
Size (mm)	190x340x60
Width (mm)	60
Bearing No.	30238JR
Grease lub.	1000
Bearing number	30238JR
(Refer.)Mass(kg)	21.9
Bore Diameter (mm)	190
Outer Diameter (mm)	340
Calculation factor (e)	0,44
Calculation factor (Y0)	0,76
(Oil) Lubrication Speed	1300 r/min
(Grease) Lubrication Speed	1000 r/min
Basic static load rating (C0)	1030 kN
Basic dynamic load rating (C)	729 kN