



Bearing No. HR30238J

D	340 mm
d	190 mm
T	60 mm
B	55 mm
C	46 mm
a	64,4 mm
e	0.44
Cr	77500
Y0	0.76
db	223
da	217
Y1	1.4
B_	55
Sb	14
C0	1080
Sa	9
D_	340
Z_	21
C_	46
C0r	111000
DA_	37.969
Iso	4GB
DE_	304.423
D_b	318
DI_	229.261
SBRG	2
SDM_	266.842
D_a2	302
KBRG	3111
yobi	HR30238J

D_a1	322
mass	21.4
TC-RA	563.836
r min.	5 mm
Weight	21,4 Kg
TC-DA1	39.352
TC-DA2	36.586
TC-SLR	40
Da min	302 mm
LangID	1
ALPHA_	16.173
Db min.	318 mm
Oil rpm	1300
db max.	223 mm
Da max.	322 mm
ra max.	4 mm
hidYobi	HR30238J
da min.	217 mm
T-ALP21	32
rb max.	3 mm
T-ALP22	20
T-ALP23	40
GRS rpm	1000
inner r	5
outer r	4
r1 min.	4 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	4
outer rb	3
TC-BET22	0

Size (mm)	190x340x60
Width (mm)	60
Prod_Type3	TRBSR_MD_A
Bearing number	HR30238J
Bore Diameter (mm)	190
Outer Diameter (mm)	340
Calculation factor (e)	0,44
Calculation factor (Y0)	0,76
(Oil) Lubrication Speed	1300 r/min
(Grease) Lubrication Speed	1000 r/min
Basic dynamic load rating (C)	760 kN
Basic static load rating (C0)	1080 kN