



Bearing No. 30248

D	440 mm
d	240 mm
T	79 mm
B	72 mm
C	60 mm
a	85,1 mm
e	0.44
Cr	101000
Y0	0.74
db	288
da	267
Y1	1.4
B_	72
Sb	19
C0	1400
Sa	11
D_	440
Z_	18
C_	60
C0r	142000
DA_	47.678
Iso	-
DE_	389.307
D_b	408
DI_	295.53
SBRG	2
SDM_	342.419
D_a2	384
KBRG	3111
yobi	30248

D_a1	422
mass	45.2
TC-RA	706.895
r min.	5 mm
Weight	45,2 Kg
TC-DA1	49.337
TC-DA2	46.018
TC-SLR	48
Da min	384 mm
LangID	1
ALPHA_	16.5
Db min.	408 mm
Oil rpm	1000
db max.	288 mm
Da max.	422 mm
ra max.	4 mm
hidYobi	30248
da min.	267 mm
T-ALP21	33
rb max.	3 mm
T-ALP22	0
T-ALP23	0
GRS rpm	750
inner r	5
outer r	4
r1 min.	4 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	4
outer rb	3
TC-BET22	0

Size (mm)	240x440x79
Width (mm)	79
Prod_Type3	TRBSR_MD_A
Bearing number	30248
Bore Diameter (mm)	240
Outer Diameter (mm)	440
Calculation factor (e)	0,44
Calculation factor (Y0)	0,74
(Oil) Lubrication Speed	1000 r/min
(Grease) Lubrication Speed	750 r/min
Basic dynamic load rating (C)	990 kN
Basic static load rating (C0)	1400 kN