



Bearing No. 30248R

C	60 mm
e	0.42
d	240 mm
D	440 mm
T	79 mm
B	72 mm
a	82,7 mm
Y0	0.79
Y1	1.43
Cu	191
Cr	1540
C0r	1790
a(mm)	82.7
r min.	5 mm
da max	287 mm
Da min	377 mm
r(min)	5
Weight	49,5 Kg
r1(min)	4
db(max)	287
da(min)	262
Sb(min)	18
Da(max)	422
Sa(min)	14
Da(min)	377
ra(max)	4
rb(max)	3
Db(min)	409
rb max.	3 mm
ra max.	4 mm

Db min.	409 mm
Da max.	422 mm
da min.	262 mm
r2 min.	4 mm
Oil lub.	980
Size (mm)	240x440x79
Width (mm)	79
Bearing No.	30248R
Grease lub.	730
Bearing number	30248R
(Refer.)Mass(kg)	49.5
Bore Diameter (mm)	240
Outer Diameter (mm)	440
Calculation factor (e)	0,42
Calculation factor (Y0)	0,79
(Oil) Lubrication Speed	980 r/min
(Grease) Lubrication Speed	730 r/min
Basic static load rating (C0)	1790 kN
Basic dynamic load rating (C)	1230 kN