



Bearing No. 30252

D	480 mm
d	260 mm
T	89 mm
B	80 mm
C	67 mm
a	94,5 mm
e	0.44
Cr	121000
Y0	0.74
db	316
da	302
Y1	1.4
B_	80
Sb	22
C0	1700
Sa	12
D_	480
Z_	18
C_	67
C0r	174000
DA_	52.307
Iso	-
DE_	426.725
D_b	447
DI_	324.346
SBRG	2
SDM_	375.536
D_a2	421
KBRG	3111
yobi	30252

D_a1	458
mass	60.7
TC-RA	776.198
r min.	6 mm
Weight	60,7 Kg
TC-DA1	54.174
TC-DA2	50.439
TC-SLR	54
Da min	421 mm
LangID	1
ALPHA_	16.5
Db min.	447 mm
Oil rpm	900
db max.	316 mm
Da max.	458 mm
ra max.	5 mm
hidYobi	30252
da min.	293 mm
T-ALP21	33
rb max.	4 mm
T-ALP22	0
T-ALP23	0
GRS rpm	670
inner r	6
outer r	5
r1 min.	5 mm
hidTable	ecat_NSTPRM
TC-BET23	0
TC-BET21	4
inner ra	5
outer rb	4
TC-BET22	0

Size (mm)	260x480x89
Width (mm)	89
Prod_Type3	TRBSR_MD_A
Bearing number	30252
Bore Diameter (mm)	260
Outer Diameter (mm)	480
Calculation factor (e)	0,44
Calculation factor (Y0)	0,74
(Oil) Lubrication Speed	900 r/min
(Grease) Lubrication Speed	670 r/min
Basic dynamic load rating (C)	1190 kN
Basic static load rating (C0)	1700 kN