



Bearing No. HR30208J

| | |
|------|----------|
| a | 16,6 mm |
| e | 0.38 |
| d | 40 mm |
| D | 80 mm |
| T | 19,75 mm |
| B | 18 mm |
| C | 16 mm |
| B_ | 18 |
| da | 51 |
| Y0 | 0.88 |
| C0 | 70 |
| D_ | 80 |
| Sb | 3.5 |
| Sa | 3 |
| db | 48 |
| Z_ | 17 |
| Y1 | 1.6 |
| C_ | 16 |
| Cr | 6450 |
| DE_ | 69.73 |
| Iso | 3DB |
| DI_ | 50.032 |
| C0r | 7150 |
| DA_ | 10.029 |
| D_b | 75 |
| D_a2 | 69 |
| SBRG | 2 |
| SDM_ | 59.881 |
| D_a1 | 71 |
| yobi | HR30208J |
| | |

| | |
|----------|-------------|
| KBRG | 3111 |
| mass | 0.437 |
| TC-RA | 150 |
| r min. | 1,5 mm |
| LangID | 1 |
| TC-DA2 | 9.589 |
| Da min | 69 mm |
| TC-SLR | 12.7 |
| ALPHA_ | 14.036 |
| TC-DA1 | 10.469 |
| Weight | 0,437 Kg |
| T-ALP22 | 4 |
| da min. | 51 mm |
| r1 min. | 1,5 mm |
| T-ALP21 | 28 |
| db max. | 48 mm |
| hidYobi | HR30208J |
| rb max. | 1,5 mm |
| T-ALP23 | 20 |
| Da max. | 71 mm |
| Oil rpm | 6300 |
| GRS rpm | 4800 |
| ra max. | 1,5 mm |
| inner r | 1.5 |
| Db min. | 75 mm |
| outer r | 1.5 |
| inner ra | 1.5 |
| hidTable | ecat_NSTPRM |
| outer rb | 1.5 |
| Category | Bearings |
| TC-BET23 | 0 |
| TC-BET21 | 4 |
| | |

| | |
|-------------------------------|-------------|
| TC-BET22 | 0 |
| Inventory | 0.0 |
| Size (mm) | 40x80x19.75 |
| Prod_Type3 | TRBSR_MD_A |
| Width (mm) | 19,75 |
| Product Group | B04334 |
| Bearing number | HR30208J |
| Weight / Kilogram | 0.43 |
| Manufacturer Name | NSK |
| Bore Diameter (mm) | 40 |
| Outer Diameter (mm) | 80 |
| Minimum Buy Quantity | N/A |
| Calculation factor (e) | 0,38 |
| (Oil) Lubrication Speed | 6300 r/min |
| Calculation factor (Y0) | 0,88 |
| (Grease) Lubrication Speed | 4800 r/min |
| Basic dynamic load rating (C) | 63,5 kN |
| Basic static load rating (C0) | 70 kN |