



### Bearing No. 6009ZZ

r	1
d	45 mm
D	75 mm
B	16 mm
C	16 mm
D_	75
Z_	13
B_	16
ra	1
fo	15.3
C0	15.2
DI_	52.269
DE_	69.731
DA_	8.731
D_a	70
SRE	4.52
SRI	4.52
SRIN	-0.02
Noun	Bearing
bomp	0
Bore	1.772 Inch   45 Millimeter
SREN	-0.02
mass	0.241
SRIX	0.02
SREX	0.02
SBRG	10
yobi	6009ZZ
KBRG	6141
SDM_	61

ALPHA_	0
da min	50
C_conv	20900
LangID	1
da max	53,5 mm
UNSPSC	31171504
r min.	1 mm
Weight	0,241 Kg
da min.	50 mm
GRS rpm	9000
Da max.	70 mm
ra max.	1 mm
hidYobi	6009ZZ
hidTable	ecat_NSRDGB
Category	Single Row Ball Bearing
Enclosure	2 Metal Shields
Snap Ring	No
Inventory	0.0
Size (mm)	45x75x16
Width (mm)	16
bore type:	Round
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	0.245
closure type:	Double Shielded
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6009ZZ
Keyword String	Ball
bore diameter:	45 mm
overall width:	16 mm
Rolling Element	Ball Bearing

Precision Class	ABEC 1   ISO P0
Outer Race Width	0.63 Inch   16 Millimeter
Outside Diameter	2.953 Inch   75 Millimeter
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Long Description	45MM Bore; 75MM Outside Diameter; 16MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Weight / Kilogram	0.11
outside diameter:	75 mm
Manufacturer Name	NSK
Bore Diameter (mm)	45
Internal Clearance	C0-Medium
internal clearance:	Normal Clearance
Outer Diameter (mm)	75
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
manufacturer upc number:	029176012952
Manufacturer Item Number	6009ZZ
Internal Special Features	No
(Grease) Lubrication Speed	9 000 r/min
Basic static load rating (C0)	15,2 kN
Basic dynamic load rating (C)	20,9 kN
Maximum Capacity /	No

Filling Slot	
--------------	--