



Bearing No. 6009ZZ

D	75 mm
d	45 mm
B	16 mm
C	16 mm
rn	0,5 mm
Bore	1.772 Inch 45 Millimeter
Noun	Bearing
da max	52,5 mm
UNSPSC	31171504
Weight	0,237 Kg
r min.	1 mm
ra max.	1 mm
da min.	50 mm
Da max.	70 mm
Category	Single Row Ball Bearing
Size (mm)	45x75x16
Snap Ring	No
Inventory	0.0
Enclosure	2 Metal Shields
Width (mm)	16
bore type:	Round
Weight / LBS	0.53572
Inch - Metric	Metric
closure type:	Double Shielded
Product Group	B00308
Cage Material	Steel
bore diameter:	45 mm
Keyword String	Ball
overall width:	16 mm

cage material:	Steel
fillet radius:	1 mm
Other Features	Deep Groove Shell Alvania Prelubricated
Bearing number	6009ZZ
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Long Description	45MM Bore; 75MM Outside Diameter; 16MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Manufacturer URL	http://www.ntnamerica.com
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
Outside Diameter	2.953 Inch 75 Millimeter
precision rating:	ISO Class 0
outer ring width:	16 mm
inner ring width:	16 mm
Weight / Kilogram	0
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
outside diameter:	75 mm
Bore Diameter (mm)	45
Internal Clearance	C0-Medium
snap ring included:	Without Snap Ring
Outer Diameter (mm)	75

internal clearance:	CN
Minimum Buy Quantity	N/A
static load capacity:	11500 N
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	9200 rpm
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	21000 N
Internal Special Features	No
(Grease) Lubrication Speed	9 200 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	15,1 kN
Basic dynamic load rating (C)	21 kN
Maximum Capacity / Filling Slot	No