



Bearing No. 16006

r	0.3
d	30 mm
D	55 mm
B	9 mm
C	9 mm
fo	15.2
D_	55
B_	9
ra	0.3
Z_	12
C0	7.35
DI_	36.15
SRE	3.29
D_a	53
DE_	48.85
SRI	3.29
DA_	6.35
SREN	-0.02
Noun	Bearing
SRIN	-0.02
bomp	0
SRIX	0.02
yobi	16006
mass	0.087
SDM_	42.5
KBRG	6101
SREX	0.02
SBRG	0
Bore	1.181 Inch 30 Millimeter

r min.	0,3 mm
UNSPSC	31171504
ALPHA_	0
LangID	1
C_conv	11200
da min	32
Weight	0,087 Kg
ra max.	0,3 mm
Oil rpm	15000
da min.	32 mm
hidYobi	16006
Da max.	53 mm
GRS rpm	13000
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	5.0
Enclosure	Open
Snap Ring	No
Size (mm)	30x55x9
Prod_Type3	DGBB_SR_OT
bore type:	Round
Width (mm)	9
Weight / LBS	0.176
closure type:	Open
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	16006
Keyword String	Ball
overall width:	9 mm
bore diameter:	30 mm
Precision Class	ABEC 1 ISO P0

Rolling Element	Ball Bearing
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.354 Inch 9 Millimeter
Outside Diameter	2.165 Inch 55 Millimeter
Long Description	30MM Bore; 55MM Outside Diameter; 9MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
outside diameter:	55 mm
Weight / Kilogram	0.08
Manufacturer Name	NSK
Bore Diameter (mm)	30
Internal Clearance	C0-Medium
Outer Diameter (mm)	55
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	15 000 r/min
manufacturer upc number:	029176059414
Internal Special Features	No
(Grease) Lubrication Speed	13 000 r/min
Basic static load rating (C0)	7,35 kN
Basic dynamic load rating (C)	11,2 kN
Maximum Capacity / Filling Slot	No