



Bearing No. NUP2208

F	50 mm
D	80 mm
J	54,2 mm
C	23 mm
E	70 mm
B	23 mm
d	40 mm
Fw	50 mm
d1	54.2 mm
Noun	Bearing
Bore	1.575 Inch 40 Millimeter
Width	0.906 Inch 23 Millimeter
UNSPSC	31171547
ra max	1 mm
Da max	73.5 mm
da min	46.5 mm
rs min	1.1 mm
dc min	56 mm
r min.	1,1 mm
Weight	0,49 Kg
r1 min.	1,1 mm
r1s min	1.1 mm
Profile	Complete with Outer and Inner Ring
Category	Cylindrical Roller Bearing
Retainer	Yes
Separable	No
Inventory	0.0

Snap Ring	No
Size (mm)	40x80x23
Width (mm)	23
Nlim (oil)	10,000 rpm
Bore Profile	Straight
Weight / LBS	1.129
Nlim (grease)	8,500 rpm
Product Group	B04144
Inch - Metric	Metric
Cage Material	Steel
Relubricatable	Yes
Other Features	1 Rib Inner Ring with Side Plate 2 Rib Outer Ring Cage On Outer Ring ID
Bearing number	NUP2208
Dynamic load, C	58 kN
Static load, C0	62 kN
Precision Class	RBEC 1 ISO P0
Rolling Element	Cylindrical Roller Bearing
Outside Diameter	3.15 Inch 80 Millimeter
Manufacturer URL	http://www.ntnamerica.com
Long Description	40MM Bore; Straight Bore Profile; 80MM Outside Diameter; 23MM Width; Steel Cage Material; RBEC 1 ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C0-Medium Internal Clearance; Retai
Weight / Kilogram	0.511
Manufacturer Name	NTN

Internal Clearance	C0-Medium
Bore Diameter (mm)	40
Outer Diameter (mm)	80
Minimum Buy Quantity	N/A
Fatigue limit load, Cu	7.6 kN
Mass (without HJ ring)	0.51 kg
Radial clearance class	CN
Harmonized Tariff Code	8482.50.00.00
Manufacturer Item Number	NUP2208
Number of Rows of Rollers	Single Row
(Grease) Lubrication Speed	8 500 r/min
Basic static load rating (C0)	62 kN
Basic dynamic load rating (C)	58 kN
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C