



Bearing No. HJ-223016

D	47,625 mm
C	25,4 mm
Da	42.88
Cr	25.4
Fw	34,925 mm
Cu	10.1
C0r	64.1
Noun	Bearing
Bore	1.375 Inch 34.925 Millimeter
Width	1 Inch 25.4 Millimeter
UNSPSC	31171512
Weight	0,127 Kg
rs(min)	1.02
r5 min.	1,02 mm
Category	Needle Non Thrust Roller Bearing
Oil lub.	13000
Retainer	Yes
Enclosure	Open
Separable	No
Inventory	5.0
Size (mm)	34.925x47.625x25.4
Component	Roller Assembly with Outer Ring - No Inner Ring
Width (mm)	25,4
Closed End	No
Grease lub.	8200
Bearing No.	HJ-223016
Weight / LBS	0.28

Product Group	B04144
Inch - Metric	Inch
Self Aligning	No
Keyword String	Needle
Bearing number	HJ-223016
Other Features	2 Rib Outer Ring Steel Cage Heavy Duty Oil Hole
Thrust Bearing	No
Relubricatable	Yes
Rolling Element	Needle Roller Bearing
(Refer.)Mass(kg)	0.127
Outside Diameter	1.875 Inch 47.625 Millimeter
Long Description	1-3/8" Bore; 1-7/8" Outside Diameter; 1" Width; Needle Roller Bearing; Roller Assembly with Outer Ring - No Inner Ring; Open Enclosure; No Self Aligning; Yes Retainer; Single Row of Rol
Manufacturer URL	http://www.koyousa.com
Weight / Kilogram	0.13
Manufacturer Name	KOYO
Bore Diameter (mm)	34,925
Outer Diameter (mm)	47,625
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
Used with inner ring No.	IR-182216
Manufacturer Item Number	HJ-223016
Number of Rows of Rollers	Single Row
(Grease) Lubrication	13000 r/min

Speed	
Clearance fit S(h6)(max.)	34.925
Clearance fit S(h6)(min.)	34.910
Clearance fit H(H7)(max.)	47.650
Clearance fit H(H7)(min.)	47.625
Basic dynamic load rating (C)	39,8 kN
Basic static load rating (C0)	64,1 kN
Tight transition fit S(f6)(max.)	34.900
Tight transition fit S(f6)(min.)	34.884
Tight transition fit H(N7)(max.)	47.617
Tight transition fit H(N7)(min.)	47.592